



Maintenance



The complete solution for concrete needs.

**SURFKOAT™**

Surface Coatings, Inc. 134 Davis Street Portland, TN 37148  
Ph: 615.323.9461 Fax: 615.323.9816 www.SurfKoat.com

© 2011 by Surface Coatings, Inc. All rights reserved.

**APPLICATION ACCESSORIES**

Surface Coatings, Inc. also offers a complete line SP Systems industrial sprayers, as well as many other application accessories including but not limited to:

- Acid Stain Sprayers
- Acetone Sprayers
- Concrete Sealer Sprayers
- Accessories for Sprayers
- Rollers (various sizes)
- Roller Frame Assemblies
- Acid Scrub Brushes
- and much more...



Proudly Distributed By:



**Maintenance**

Interior Wax/Polish Systems

**Product Guide**



**SURFKOAT™**

Surface Coatings, Inc.

Manufacturers of Industrial and Decorative Concrete Materials

# Cherry SURF WAX

# TOP KOAT HIGH PERFORMANCE

Cherry Surf-Wax is a cherry scented water based acrylic floor wax. It is perfect for small areas as well as large commercial areas as it can be applied by mop or high speed burnishing. Cherry Surf-Wax yields rapid gloss build along with superior long term wear characteristics. It's superior resistance to wet and dry traffic wear can yield a smooth polished look for months without maintenance. Cherry Surf-Wax should be used on any sealed surface where a rapidly high gloss build and superior maintenance properties are desired. Should be considered an economical workhorse.

***\*Also Available in a Matte Finish Formula!***

Solids.....	21%
Drying Time.....	1-2 hours
Re-Coat Time.....	2-3 hours
Foot Traffic.....	12-24 hours
Wheel Traffic.....	24-48 hours
Application Temp.....	40°F - 85°F
Wet Appearance.....	Milky White
Dry Appearance.....	Crystal Clear
VOC Content.....	none
Blush Resistance.....	Excellent
Solvent Resistance.....	Good
Concrete Adhesion.....	Superior (over sealed surfaces)

Top Coat is a high performance cherry scented water based acrylic floor finish. It is perfect for small areas as well as large commercial areas as it can be applied by mop or high speed burnishing. Top Coat yields rapid high gloss build along with superior long term wear characteristics. It's superior resistance to wet and dry traffic wear can yield a smooth polished look for months without maintenance. Top Coat should be used on any sealed surface where a rapidly high gloss build and superior maintenance properties are desired. Use Top Coat for extreme sheen and durability.

Solids.....	28%
Drying Time.....	1-2 hours
Re-Coat Time.....	2-3 hours
Foot Traffic.....	12-24 hours
Wheel Traffic.....	24-48 hours
Application Temp.....	40°F - 85°F
Wet Appearance.....	Milky White
Dry Appearance.....	Crystal Clear
VOC Content.....	none
Blush Resistance.....	Excellent
Solvent Resistance.....	Good
Concrete Adhesion.....	Superior (over sealed surfaces)



Surface Koatings, Inc.  
134 Davis Street  
Portland, TN 37148  
Ph: 615.323.9461 Fax: 615.323.9816